

RS-485 BACnet/Modbus Airflow/Temperature Transmitter Module w/Contact Closure Airflow Alarm



- √ Provide continuous verification of airflow rates
- √ Ideal for monitoring applications
- √ Connect to an application controller to maintain airflow rates and/or temperature
- √ Demonstrate compliance with ASHRAE Standards 62.1, 90.1 and 189.1
- √ Satisfy LEED prerequisites and document code compliance
- √ Improve indoor air quality and thermal comfort
- √ Save energy

The GF-N3000 can be provided with a single integrated IAT-DI duct probe or, one or two integrated IAT-UI or IAT-US universal mount probes.

The GF-N3000 provides a network connection for the average

- Compatible with GreenTrol IAT integrated thermal dispersion airflow/temperature sensors
- LCD with pushbutton user interface standard
- Measures airflow and temperature
- Airflow and system status notification alarms
- RS-485 network connection can be field configured for BACnet MS/TP or Modbus RTU
- Airflow can be assigned to one or two airflow locations when more than one probe is provided
- Contact closure relay can be assigned to notification alarms
- “Plug and play” operation
- Field adjust wizard facilitates airflow adjustment when conditions warrant.
- Fully field configurable

airflow of one or two probes. It can also be configured to output the airflow of the second probe for applications where two probes are installed in separate locations. Temperature and notification alarms are available via the network. The airflow and temperature of individual sensor nodes are available via the network, if desired. A contact closure relay is provided that can be assigned to the notification alarms. The GF-N3000 can be configured for I-P or SI units of measure.

Although the transmitter is “plug and play” and operates on power up, it is fully configurable in the field using the pushbutton interface and LCD.

GF-N3000 Transmitter Module Technical Specifications

Functionality

Airflow Measurement: Provides the average airflow rate of one or two probes, or optionally of individual probes, in FPM [m/s] or CFM [LPS] on the LCD and via the network.

Temperature Measurement: Provides the velocity weighted or arithmetic average temperature in °F [°C] on the LCD and to analog output AO2 when AO2 is assigned to temperature.

Notification Alarms

High/Low Airflow Alarm

System Trouble Alarm

Note: Alarms can be assigned to the contact closure relay

User Interface

Display: 16-character alpha-numeric LCD

Navigation: 4-button interface

Integrated Sensor Capability

Type: Accepts GreenTrol IAT-DI, IAT-UI and IAT-US Thermal Dispersion Airflow and Temperature Measurement Probe (required unless an external MS/TP airflow measurement device is provided). See appropriate IAT product data sheet for probe information.

Available Configurations: IAT-DI Probes

Single Probe: 1 probe x 1 or 2 sensor nodes/probe

Available Configurations: IAT-UI and IAT-US Probes

Single Probe: 1 probe x 1 sensor node/probe

Dual Probe: 2 probes x 1 sensor node/probe

Network Connection

N1

Type: Non-isolated, field selectable MS/TP BACnet master or Modbus RTU connection (provide separate transformer to each GF-N1000-DI or an RS-485 network isolator if isolation is required)

B.A.S. Object/Register Read/Write Access: Yes

Device Load: 1/8 load

Supported Baud Rates: 9.6, 19.2, 38.4 and 76.8 kbaud

Contact Closure Relay

R1

Type: Dry contact w/ onboard jumper to drive a remote LED

Assignment: OAC alarms or Control Mode

Status: Normally Open (N.O.)

Rating: 30 VDC or 24 VAC @ 3 amp. max.

Environmental Limits, Power Requirements & Dimensions

Environmental Limits

Temperature: -20 to 120 °F [-28.9 to 48.9 °C]

Humidity: 5 to 95%

Important: Provide a weather-proof enclosure if the transmitter module is mounted outdoors

Power Requirement: 24 VAC (22.8 to 26.4 under load) @8.5V-A

Dimensions: 3.57H x 6.00W x 1.50D in. [90.7 x 152.4 x 38.1 mm]

Universal Standoff Mount Thermal Dispersion Airflow/Temperature Measurement Probe for Outdoor Intakes, Plenums and Fan Cabinets



- Compatible with GreenTrol transmitters and controllers that accept IAT integrated sensors
- Thermal dispersion technology
- Calibrated from 0 to 3,000 FPM
- Stable bead-in-glass thermistor sensors
- NIST traceable airflow and temperature measurement
- Accurate and repeatable
- Designed for openings up to 8 square feet
- Universal mounting design facilitates ordering and installation
- Three probe lengths available
- Aluminum probe construction
- FEP plenum rated cable with terminal DIN connector plug provided

Typical Installations:

- Rooftop air handler outdoor air intakes
- Fan cabinets and powered exhaust boxes
- Unit ventilator outdoor air intakes
- ERV cabinet and wheel intake/exhaust paths

IAT (integrated airflow/temperature) sensors reduce cost by eliminating the redundancy of a separate transmitter for airflow and temperature measurement. The processing circuitry and firmware is integrated into one of GreenTrol's microprocessor-based transmitters or application specific controllers.

The IAT-US airflow/temperature sensor is designed for mounting inside of plenums or other openings where airflow measurement is desired. One or two probes with a single sensor node are typically used. Sensor node airflow accuracy is $\pm 3\%$ of reading to NIST traceable standards. An installed accuracy of $\pm 10\%$ of reading or better can often be achieved without field adjustment. A field adjust wizard built into GreenTrol's transmitters and application specific controllers

facilitate field setup when conditions warrant.

The IAT-US sensor probe uses the principal of thermal dispersion to determine the airflow rate. Thermal dispersion is ideal for HVAC applications that typically require measurement of low air velocities. Each sensing node uses two thermistors to determine airflow. One thermistor is self-heated above ambient while a second thermistor determines the ambient air temperature. The power dissipated into the airstream is directly related to the airflow rate.

Each thermistor body is a hermetically sealed bead-in-glass probe. Bead-in-glass thermistors have demonstrated extreme stability and superior performance over chip type thermistors used by other manufacturers. The bead-in-glass sensor used has been time tested for over 35 years by GreenTrol's sister company, EBTRON. Thermistors are potted in a waterproof sensor assembly and are designed for years of trouble-free operation.

Each sensing node is individually calibrated at 7 points in high-performance wind tunnels. Transmitters and controllers measure and process each individual sensor node

IAT-US Technical Specifications

Functionality

Airflow Measurement: Provides individual sensor node airflow rates to compatible GreenTrol transmitters and controllers
Temperature Measurement: Provides individual sensor node temperatures to compatible GreenTrol transmitters and controllers

Airflow/Temperature Measurement Probe

Type: -US Universal Insertion Mount Thermal Dispersion Airflow and Temperature Measurement Probe

Available Configurations

Single Probe: 1 probe x 1 sensor node/probe
Dual Probe: 2 probes x 1 sensor node/probe

Sensing Node Sensors

Self-heated sensor: Precision, hermetically sealed, bead-in-glass thermistor probe
Temperature sensor: Precision, hermetically sealed, bead-in-glass thermistor probe

Probe Tube

Material: Mill finish 6063 aluminum

Probe Mounting Brackets

Material: 304 stainless steel

Probe Length: 6, 8 or 16 in. [152.4, 203.2 or 406.4 mm] (adjustable)

Sensing Node Housing

Material: Glass-filled Polypropylene
Sensor Potting Materials: Waterproof marine epoxy

Sensing Node Internal Wiring

Material: Kynar® coated copper

Probe to Transmitter Cables

Material: FEP jacket, plenum rated CMP/CL2P, UL/cUL listed, -67 to 392 °F [-55 to 200 °C], UV tolerant
Standard Lengths: 10, 25 and 50 ft. [3.1, 7.6 and 15.2 m]
Connecting Plug: 0.60" [15.24 mm] nominal diameter

Airflow Measurement

Sensor Accuracy: ±3% of reading to NIST-traceable airflow standards
Averaging Method: Independent, arithmetic average
Installed Accuracy: Typically better than ±10% of reading in ducts/openings ≤ 8 sq ft [0.74 sq m]
Calibrated Range: 0 to 2,000 fpm [0 to 10.16 m/s]
Calibration Points: 7

Temperature Measurement

Averaging Method: Independent, velocity weighted
Accuracy: ±0.15°F [0.08 °C]

Environmental Limits & Power Requirements

Environmental Limits

Temperature: -20 to 160 °F [-28.9 to 71.1 °C]

Note: Temperature limits for operation may be limited by the transmitter or controller selected

Humidity: 0 to 100%

Power Requirement: Power is provided by the transmitter or controller and is included in the transmitter/controller power requirement specification